Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



.1	Product identifier	
	Product name	316L <15 μm
		GMP 316L
	Unique Formula Identifier (UFI)	Not assigned
	Nanoform	Not assigned
1.2	Relevant identified uses of the substance or mixture	
	and uses advised against	
	Identified Use(s)	Metal injection moulding
	Uses advised against	Any other use.
1.3	Details of the supplier of the safety data sheet	
	Company Identification	Globus Metal Powders Ltd.
		Materials Processing Institute, Eston Road, Middlesbrough, TS6 6US
	Telephone	+44(0)164 238 2000
	E-mail (competent person)	gmp@globusmetalpowders.com
1.4	Emergency telephone number	
	Emergency Phone No.	999 / 111 (or local emergency number)
	Languages spoken	English (or local language)
SECT	TON 2: Hazards identification	
2.1	Classification of the substance or mixture	
2.1.1	Regulation (EC) No. 1272/2008 (CLP)	Skin Sens. 1; H317
		Carc. 2; H351
		STOT RE 1; H372
		Aquatic Chronic 3; H412
2.2	Label elements	According to Regulation (EC) No. 1272/2008 (CLP)
	Product name	316L < 15 μm
	Contains:	Nickel
	Hazard Pictogram(s)	\wedge
		▼ ▼
	Signal Word(s)	DANGER
	Signal Word(s) Hazard Statement(s)	DANGER H317: May cause an allergic skin reaction.
		H317: May cause an allergic skin reaction.
		H317: May cause an allergic skin reaction. H351: Suspected of causing cancer.
		H317: May cause an allergic skin reaction. H351: Suspected of causing cancer. H372: Causes damage to organs through prolonged or repeated exposure.
	Hazard Statement(s)	 H317: May cause an allergic skin reaction. H351: Suspected of causing cancer. H372: Causes damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects.
	Hazard Statement(s)	 H317: May cause an allergic skin reaction. H351: Suspected of causing cancer. H372: Causes damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects. P201: Obtain special instructions before use.
	Hazard Statement(s)	 H317: May cause an allergic skin reaction. H351: Suspected of causing cancer. H372: Causes damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects. P201: Obtain special instructions before use. P260: Do not breathe dust.

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



P308+P313: IF exposed or concerned: Get medical advice/attention. P273: Avoid release to the environment.

Supplemental information

Not applicable

2.3 Other hazards

May form combustible dust concentrations in air. Handling of this material may generate a dust which can cause mechanical irritation of the eyes, skin nose and throat.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard classification
Nickel	10 - < 20	7440-02-0	231-111-4	Not yet assigned in the supply chain	Skin Sens. 1; H317 Carc. 2; H351 STOT RE 1; H372 Aquatic Chronic 3; H412
Manganese	1 - < 2	7439-96-5	231-105-1	Not yet assigned in the supply chain	Aquatic Chronic 2; H411

For full text of H phrases see section 16.

SECTION 4: First aid measures



```
Description of first aid measures
4.1
        Self-protection of the first aider
                                                                 Obtain special instructions before use. No action should be taken involving
                                                                 personal risk. Use personal protective equipment as required. Wear appropriate
                                                                 personal protective equipment, avoid direct contact. Ensure adequate
                                                                 ventilation. Do not breathe dust. Avoid contact with skin and eyes.
        inhalation
                                                                 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in
                                                                 a position comfortable for breathing. Get medical attention immediately.
         Skin contact
                                                                 IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation or rash
                                                                 occurs: Get medical advice/attention. Remove contaminated clothing and wash
                                                                 clothing before reuse.
        Eye contact
                                                                 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
                                                                 lenses, if present and easy to do. Continue rinsing.If irritation develops and
                                                                 persists, get medical attention.
        Ingestion
                                                                 IF SWALLOWED: Rinse mouth. Give plenty of water to drink. Do NOT induce
                                                                 vomiting. Seek medical treatment.
4.2
        Most important symptoms and effects, both acute
                                                                 May cause an allergic skin reaction. Suspected of causing cancer. Causes
        and delayed
                                                                 damage to organs through prolonged or repeated exposure.
4.3
        Indication of any immediate medical attention and
                                                                 Treat symptomatically.
        special treatment needed
```

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media

As appropriate for surrounding fire. Use CO2, dry chemical, or foam. Do not use water jet. Direct water jet may spread the fire.

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



5.2	Special hazards arising from the substance or mixture	Explosion: May form combustible dust concentrations in air. Avoid dust generation. Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Combustion products:, Carbon monoxide, Carbon dioxide and Nickel carbonyl gas.
5.3	Advice for firefighters	Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: Accidental release measures

6.1	Personal precautions, protective equipment and emergency procedures	Caution - spillages may be slippery. Ensure operatives are trained to minimise exposures. No action should be taken involving personal risk. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe dust. Ensure adequate ventilation. Remove contaminated clothing and wash all affected areas with plenty of water. Avoid dust generation. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
6.2	Environmental precautions	Avoid release to the environment. Do not allow to enter drains, sewers or water courses.
6.3	Methods and material for containment and cleaning up	Provided it is safe to do so, isolate the source of the leak. Sweep spilled substances into containers if appropriate moisten first to prevent dusting. Use non-sparking equipment when picking up flammable spill. Collect mechanically and dispose of according to Section 13. Use non-sparking tools. Ventilate the area and wash spill site after material pick-up is complete.
6.4	Reference to other sections	See Section: 8,13.

SECTION 7: Handling and storage

7.1	Precautions for safe handling	When using do not eat or drink. Provide adequate ventilation when using the material and follow the principles of good occupational hygiene to control personal exposures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and wash clothing before reuse.
7.2	Conditions for safe storage, including any incompatibilities	Keep only in original packaging. Keep in a well ventilated place. Keep container closed.
	storage temperature	Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources.
	Incompatible materials	Keep away from: acids and strong oxidising agents.
7.3	Specific end use(s)	See Section: 1.2.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Occupational exposure limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Nickel	7440-02-0	-	0.5	-	-	UK WEL
Manganese	7439-96-5	-	0.2 0.05	-	-	UK WEL Inhalable fraction Respirable fraction

Source: UK WEL: Workplace Exposure Limit (UK HSE EH40)


8.1.2 Biological Limit Value

Not established.

8.1.3 PNECs and DNELs

Not established.

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021





8.2 8.2.1	Exposure controls Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Do not breathe dust. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).
8.2.2	Individual protection measures, such as personal protective equipment	Obtain special instructions before use. Keep good industrial hygiene. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke at the work place.Do not breathe dust.
Prote	o , ,	g place, depending on concentration and quantity of the hazardous substances to chemicals should be ascertained with the respective supplier.
	Eye / face protection	Wear eye protection with side protection (EN166). Eyewash bottles should be available.
	Skin protection	Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Protective index 6, corresponding > 480 minutes of permeation time according to EN 374.
		Body protection: Wear dust-resistant protective clothing.
	Respiratory protection	Not normally required. Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely to be evolved. In case of inadequate ventilation wear respiratory protection. Recommended: EN143 Type A-P2.
	Thermal hazards	not applicable
8.2.3	Environmental exposure controls	Avoid release to the environment.
SECT	ION 9: Physical and chemical properties	

9.1	Information on basic physical and chemical properties	
	Physical state	Powder
	Colour	No information available.
	Odour	Odourless.
	Melting point/freezing point	1411-1437 °C
	Initial boiling point and boiling range	No information available.
	Flammability (solid, gas)	Explosion: May form combustible dust concentrations in air.
		Maximum explosion pressure rise (Pmax) = 2.7 bar (BS EN 14034)
		Coefficient of pressure rise (Kst) = 17 bar.m.s ⁻¹ (BS EN 14034)
		Coefficient of pressure rise (Kst) = 17 bar.m.s ⁻¹ (BS EN 14034) Maximum Rate of Pressure Rise (dP/dt)max = 63 bar.s-1 (BS EN 14034)
	l les en/leures flaveres du iliteres europasius lissite	St Class =1 (BS EN 14034)
	Upper/lower flammability or explosive limits	Layer ignition temperature = >400°C (BS EN 50281-2-1)
		LIT Value (> 400°C), minus 75°C Safety Factor = 325 °C
		MIT Value (960°C), minus 1/3 Safety Factor = 640 °C
		Capacitive & Inductive MIE = > 1000 mJ
	Flash point	No information available.
	Auto-ignition temperature	No information available.
	Decomposition temperature	No information available.
	рН	No information available.

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



Viscosity Solubility(ies) Partition coefficient: n-octanol/water Vapour pressure Relative density Vapour density Particle characteristics

Other information Explosive properties Oxidising properties Loss on Drying Moisture Content

9.2

No information available. No information available. No information available. No information available. 8.0 g/cm³ No information available. < 15 μm

May form combustible dust concentrations in air. Not oxidising. No information available. 0.0 % w/w

SECTION 10: Stability and reactivity

10.1 10.2	Reactivity Chemical stability	Stable under normal conditions. Stable under normal conditions.
-		
10.3	Possibility of hazardous reactions	Hazardous polymerisation will not occur. May form combustible dust concentrations in air.
10.4	Conditions to avoid	Hydrogen gas can be liberated when nickel or its alloys react with acids. In reduced atmospheres nickel can react with carbon monoxide to form Ni(CO)4, which is an extremely toxic gas.
10.5	Incompatible materials	Keep away from: acids and strong oxidising agents.
10.6	Hazardous decomposition products	Combustion products:, Carbon monoxide, Carbon dioxide and Nickel carbonyl
		gas.

SECTION 11: Toxicological information

11.1	Information on hazard classes as defined in Regulation (EC) No 1272/2008		
	Acute toxicity - Ingestion		Mixture: Based upon the available data, the classification criteria are not met.
			Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
	Acute toxicity - inhalation		Mixture: Based upon the available data, the classification criteria are not met.
			Calculated acute toxicity estimate (ATE) > 5 mg/L (Dust)
	Acute toxicity - Skin contact		Mixture: Based upon the available data, the classification criteria are not met.
			Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
	Skin corrosion/irritation		Mixture: Based upon the available data, the classification criteria are not met.
	Serious eye damage/irritation		Mixture: Based upon the available data, the classification criteria are not met.
	Respiratory or skin sensitisation		Mixture: Skin Sens. 1; H317: May cause an allergic skin reaction.
		Nickel	Skin Sens. 1; H317: May cause an allergic skin reaction.
			EU Harmonised Classification
			EU ECHA Registration Endpoint summary
			Skin sensitisation - Adverse effects observed (NiPERA Report, 2010)
	Germ cell mutagenicity		Mixture: Based upon the available data, the classification criteria are not met.
	Carcinogenicity		Mixture: Carc. 2; H351: Suspected of causing cancer.
		Nickel	Carc. 2; H351: Suspected of causing cancer.
			EU Harmonised Classification
			EU ECHA Registration Endpoint summary
	Reproductive toxicity		Mixture: Based upon the available data, the classification criteria are not met.
	STOT - single exposure		Mixture: Based upon the available data, the classification criteria are not met.
	STOT - repeated exposure		Mixture: STOT RE 1; H372: Causes damage to organs through prolonged or
			repeated exposure.
		Nickel	STOT RE 1; H372: Causes damage to organs through prolonged or repeated
			exposure.
			EU Harmonised Classification
			oral: NOAEL – 2.2 mg/kg/bw day (rat) (Unnamed publication, 2007)
			inhalation: LOAEC – 0.1mg/m ³ (rat) (OECD 451)

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



	Aspiration hazard	dermal: No data Mixture: Based upon the available data, the classification criteria are not met.	
11.2 11.2.1 11.2.2	Information on other hazards Endocrine disrupting properties Other information	None known None known	
SECTION 12: Ecological information			

12.1	Toxicity		Mixture: Aquatic Chronic 3; H412: Harmful to aquatic life with long lasting
			effects.
			estimated LC50 (Mixture): >10 - ≤ 100 mg/l
		Nickel	Aquatic Chronic 3; H412: Harmful to aquatic life with long lasting effects.
			EU Harmonised Classification
			NOEC: 0.057 ug/L (Birge et al. 1984)
		Manganese	Aquatic Chronic 2; H411: Toxic to aquatic life with long lasting effects.
			LC50: 0.17-15.61 mg/l (28 days) (U. S. National Library of Medicine, 2018)
12.2	Persistence and degradability		No data for the mixture as a whole.
		Nickel	Not applicable for inorganic substances.
		Manganese	Not applicable for inorganic substances.
12.3	Bioaccumulative potential		No data for the mixture as a whole.
		Nickel	Low bioaccumulation potential.
			BCF: 45 (Alikhan et al. 1989)
		Manganese	Low bioaccumulation potential.
			BCF: 19 (SOREN NORDAHL HANSEN, et.al. 1995)
12.4	Mobility in soil		No data for the mixture as a whole.
		Nickel	The product is predicted to have high mobility in soil.
			Log Kp: 4.51 (Elbaz-Poulichet et al. 1996)
		Manganese	The product is predicted to have low mobility in soil.
			Kd: ~994 (OECD 106)
12.5	Results of PBT and vPvB assessment		Not classified as PBT or vPvB.
12.6	Endocrine disrupting properties		None known.
12.7	Other adverse effects		None known.
SECT	SECTION 13: Disposal considerations		
L	-		

13.1 Waste treatment methods

Additional information

13.2

Do not allow to enter drains, sewers or watercourses. Dispose of this material and its container as hazardous waste Disposal should be in accordance with local, state or national legislation. Avoid release to the environment.

SECTION 14: Transport information

	-	ADR/RID	IMDG	IATA/ICAO
14.1	UN number or ID number	None assigned	None assigned	None assigned
14.2	UN proper shipping name	None assigned	None assigned	None assigned
14.3	Transport hazard class(es)	None assigned	None assigned	None assigned
14.4	Packing group	None assigned	None assigned	None assigned
14.5	Environmental hazards	Not classified	Not classified as a	Not classified
			Marine Pollutant.	
14.6	Special precautions for user	See Section: 2		
14.7	Maritime transport in bulk according to IMO	No information available.	No information available.	No information available.
	instruments			

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878



SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 15.1.1 EU regulations
 Authorisations and/or restrictions on use Not restricted

15.2 Chemical Safety Assessment

Germany Water hazard class: 2

A REACH chemical safety assessment has not been carried out. Exposure scenarios for substances in this preparation are not available.

SECTION 16: Other information

The following sections contain revisions or new statements: New SDS Regulation 2020/878 format, all sections have been updated to include new information. Please review SDS with care.

References:

EU Harmonised Classification and EU ECHA registration dossier for Nickel (CAS No. 7440-02-0). ECHA registration dossier for Manganese (CAS No. 7439-96-5).

Test Result, Report Number: R001913R1V1GR, Sigma-HSE (UK) Ltd (2021).

Literature references

- 1. Birge, W.J., J.A. Black, J.F. Hobson, A.G. Westerman, and T.M. Short. 1984. Water Resources Research Institute. Kentucky University, Lexington, KY. Research Report No. 151.
- 2. U. S. National Library of Medicine. 2018. To determine long- term toxicity of test chemical on Oncorhynchus mykiss. HSDB (Hazardous Substances Data Bank); US national Library of Medicine reviewed by SRC.
- 3. Alikhan, M.A., Zia, S. 1989. Nickel uptake and regulation in a copper-tolerant Decapod, Cambarus (Fabricius) (Decapoda, Crustacea). Bull. Environ. Contam. Toxicol: 42, 94-102.
- 4. SOREN NORDAHL HANSEN, et.al. 1995. Marine Pollution Bulletin, 1995.
- Elbaz-Poulichet, F., Garnier, J.M., Guan, D.M., Martin, J.M., Thomas, A.J. 1996. The conservative behaviour of Trace metals (Cd, Cu, Ni, Pb) and As in the surface plume of stratified estuaries: example of the Rhome River (France). Estuarine, Coastal and Shelf Science: 42, 289-310.

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification procedure
Skin Sens. 1; H317	Threshold Calculation
Carc. 2; H351	Threshold Calculation
STOT RE 1; H372	Threshold Calculation
Aquatic Chronic 3; H412	Summation Calculation

LEGEND

ADR	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	CAS: Chemical Abstracts Service
DNEL	Derived no effect level
EC	EC: European Community
EN	European Standard
EU	European Union
IATA	IATA: International Air Transport Association
ICAO/IATA	ICAO: International Civil Aviation Organization / IATA: International Air Transport Association
IMDG	IMDG: International Maritime Dangerous Goods
LC50	Lethal concentration 50
LD50	Lethal dose 50
LOAEC	Lowest Observed Adverse Effect Concentration
LTEL	Long term exposure limit

^{15.1.2} National regulations

Version: 3.0 Revision date: 3rd June 2024 Date of First Issue 4th May 2021





NOEC	No Observed Effect Concentration
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	PBT: Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short term exposure limit
TWA	Time Weighted Average
UN	United Nations
vPvB	very Persistent and very Bioaccumulative
WGK	Wassergefährdungsklasse (Germany) / water hazard class

Hazard classification / Classification code:	Hazard Statement(s)
Skin Sens. 1; Skin Sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carc. 2; Carcinogenicity, Category 2	H351: Suspected of causing cancer.
STOT RE 1; Specific target organ toxicity — repeated exposure, Category	H372: Causes damage to organs through prolonged or repeated
1	exposure.
Aquatic Chronic 2; Hazardous to the aquatic environment, Chronic ,	H411: Toxic to aquatic life with long lasting effects.
egory 2 atic Chronic 3; Hazardous to the aquatic environment, Chronic , egory 3	H412: Harmful to aquatic life with long lasting effects.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Globus Metal Powders Ltd. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Globus Metal Powders Ltd. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

Exposure Scenarios are not applicable